

## Turntable TT 2.0 SI

### Technical Data

Diameter		2.0 m
Permissible load		1000 kg
Point load		250 kg (at area of 10cm x 10cm)
Total height	min.	130 mm
Material carrier plate		stainless steel
Rotating speed adjustable between		0.3 to 2.5 rpm
Rotating angle		+400°/-200°
Positioning accuracy		+/- 0.5°
Motor		Brushless DC motor 200 W
Interference suppression:		20 dB under limits EN 55022 class B
Turntable drive		Toothed belt drive, worm gear
Control cable		Fibre optic lines
Remote control via		IEEE interface
Current consumption	max.	2 A
Voltage		208-230 VAC, 50/60 Hz, single phase
Concentricity tolerance		+/- 3 mm
Elevation tolerance less than		5 mm
Ground plane connecting every		50 mm
Square border interface		2.3 m x 2.3 m
(Easy fitting into Groundplane of chamber)		
Temperature range		+10°C to +35°C
Total weight	approx.	380 kg
Accessories		Interface to SCU/MCU/NCD Controller 1.5 m power supply cable Service manual



### Brief description

The turntable **TT 2.0 SI** is especially designed for flush mounted installation in semi anechoic electromagnetic absorption chambers. The carrier plate is made of stainless steel.

A 285 mm diameter opening in the centre of the turntable provides the capability to insert power supply for testing.

The **IEEE 488.2 (GPIB) bus** provides an additional control option for all functions, when operated with the **SCU/MCU or NCD Controller**.

## Turntable TT 2.0 SI



Information presented enclosed is subject to change as product enhancements are made regularly.  
Pictures included are for illustration purposes only and do not represent all possible configurations.